

Lumina 200 Bulb



features & benefits

*#00534A, Tungsten Halogen (Quartz)
200T3QCL, 130 volt, 200 watts, T3, re-
placement bulb for Lumina 200*

LUM-200-BLB

Important Safety Instructions: 8800-6-3

Read all instructions

WARNING! To reduce the risk of FIRE, ELECTRIC SHOCK OR INJURY TO PERSONS:

- Min distance to lighted object: 16 feet (0.5 m)
- Input: 120V, 60 Hz
- CAUTION - RISK OF FIRE - Use 200 watt or smaller double ended halogen lamp type T-3, 120 volt.
- CAUTION - To reduce the risk of a burn during replacing bulb, disconnect power to the unit by unplugging before bulb replacement.
- Keep fixture away from combustible materials.
- Replace cracked protective shield immediately. Do not use fixture without the shield being installed.
- To reduce the risk of exposure to excessive UV radiation, do not remain under light if skin feels warm.
- Protect the fixture from impact, scratching or abrasions.
- If the cord-set becomes damaged, replace the cord-set before using fixture.

hardware specifications

graphic specifications

additional info

Assembly Instructions

To Remove Lamp

1. Turn off/unplug fixture and allow to cool before replacing lamp. Lamp gets hot quickly! Do not touch hot lamp or shade.
2. Remove the protective shield
3. Push the lamp towards one end of the lamp-holder which serves as a spring to old lamp in place. When the other end of the lamp is clear of the holder, lift the lamp out of fixture.

To Fit or Replace Lamp

1. Take the lamp out of the box taking care not to touch the lamp with your bare fingers. Oil from skin can damage lamp. Use a soft cloth when grasping lamp. Grasp the lamp with the thin wrapper covering and place one end of the bulb against the spring section of the lamp-holder and push it toward the spring side. ATTENTION! Insert lamp in the neutral lamp-holder first (see marking on fixture)
2. As the other end of the lamp clears the opposite end of the lamp-holder, insert the end down into the lamp-holder and release the tension on the spring end. Both ends of the lamp must come in contact with both ends of the lamp-holder.
3. **IMPORTANT! REINSTALL PROTECTIVE SHIELD AFTER CHANGING LAMP.**

SAVE THESE INSTRUCTIONS!

